



Transforming Transactions  
into Relationships

# NCR EasyPoint™ 41

- Small, integrated design results in a footprint which can be placed virtually anywhere in the store or business
- Flexible configurations accommodate your unique business needs
- Flexible mounting options offer freedom in installation
- Rugged, self-contained design allows placement in a variety of environments
- Ergonomic design offers ease of use for consumers



The NCR EasyPoint 41 offers consumers interactive capabilities in a compact, flexible, and reliable device. Built on industry standards, the NCR EasyPoint 41 supports both Web-based applications and standard Windows® applications and also delivers motion picture-quality video and multimedia.

NCR delivers the flexibility to configure the NCR EasyPoint 41 to your business needs by offering a range of processing, display, printing, mounting, and peripheral options.

## **Small size equals versatility**

The NCR EasyPoint 41's compact, flexible footprint enables easy installation virtually anywhere. Smaller size allows kiosk placement that maximizes consumer use and space utilization. Mounting options designed for simple installation include tabletop, shelf, pole, wall, or pedestal mounts. Custom surrounds can be created to fit your specific business need.

## **Multimedia features allow a rich consumer experience**

The NCR EasyPoint 41 provides the capability to present your message to consumers in a variety of innovative ways. Multimedia features include:

- Screen resolution options to fit your exact needs
  - 800 x 600 (12.1" screen)
  - 1024 x 768 (15" screen)
  - Supports an additional external display

# NCR EasyPoint 41

- 8MB video memory
- Capable of playing multiple audio tracks simultaneously
- Full-screen, full-motion video with fully synchronized audio playback
- MPEG II playback

## Specifications (Typical configuration):

- Touchscreen options:
  - 12.1" or 15" Color High Quality Capacitive touchscreen
  - or
  - 15" Color resistive touchscreen
- Processor options:
  - Pentium® Celeron™ 6XX MHz (socketed)
  - or
  - Pentium® III 7XX MHz (socketed)
- 64-320 MB RAM
- 10 or 20 GB hard disk drive
- 10/100-BaseT Ethernet
- Dual USB ports
- Up to 4 RS-232 serial ports
- Integrated motion sensor
- Rugged self-contained design
- PS/2 keyboard port

## Options:

- Integrated stereo speakers
- Dual PCMCIA Type 2 interface
- Cash drawer ports
- 3-Track ISO magnetic stripe reader
- Microphone port
- S-video output port
- Presentation scanner
- Integrated infrared reader
- Wireless LAN compatible
- Parallel port
- Integrated CD-ROM



## Physical specifications:

- Display terminal core module
- 12.1" screen (w/ speakers and MSR)
  - Height 14.9"/37.8 cm
  - Depth 3.1"/7.9 cm
  - Width 15.8"/40.1 cm
- 15" screen (w/ speakers and MSR)
  - Height 15.4"/39.12 cm
  - Depth 3.6"/9.14 cm
  - Width 16.8"/42.67 cm

## Environmental specifications:

- Passive cooling
- Operating temperature:
  - 32°F-113°F 0°C-45°C
- Electrical requirements
  - Universal power supply
  - 100-120v ~ 56/60Hz, 2.0A
  - 200-240v ~ 56/60Hz, 1.0A



Transforming Transactions  
into Relationships

[www.ncr.com](http://www.ncr.com)

NCR continually improves products as new technologies and components become available. NCR, therefore, reserves the right to change specifications without prior notice.

All features, functions and operations described herein may not be marketed by NCR in all parts of the world. Consult your NCR representative or NCR office for the latest information.

NCR EasyPoint is either a registered trademark or trademark of NCR Corporation in the United States and/or other countries.

All brand and product names appearing in this brochure are trademarks, registered trademarks or service marks of their respective holders.

© 2002 NCR Corporation

Patents Pending

Printed in U.S.A.

EB-1387-0302